



- UL Recognized
- Meets Military Specification
- Manufactured from 100% virgin-grade Nylon 6/6
- Self-extinguishing 94V-2
- Operating temperature range of -40°F (-4°C) to 185°F (85°C)
- Available in natural (code -9) or UV resistant black (code -0)



PART NUMBER	LENGTH <i>Inches (mm)</i>	WIDTH <i>Inches (mm)</i>	MAX BUNDLE DIAMETER <i>Inches (mm)</i>	MIN LOOP TENSILE STRENGTH	MIL SPEC	PACKAGING		
						STD.	BULK	
GT-18S1	3 1/8" (80)	0.10" (2.5)	5/8" (15)	<i>MINIATURE</i> 18 lbs (8.1 kg)	MS3367-4	100	1000	
GT-18S3	4" (100)	0.10" (2.5)	7/8" (22)			100	1000	
GT-18M1	5 1/2" (140)	0.10" (2.5)	1 3/8" (33)			100	1000	
GT-18M2	6 3/8" (160)	0.10" (2.5)	1 9/16" (40)			100	1000	
GT-18L	8" (200)	0.10" (2.5)	2" (53)			100	1000	
GT-40S	5 7/8" (150)	0.14" (3.6)	1 3/8" (35)	<i>INTERMEDIATE</i> 40 lbs (18.2 kg)	MS3367-5	100	1000	
GT-40M	8" (200)	0.14" (3.6)	2" (53)			100	1000	
GT-40L	11 1/2" (300)	0.14" (3.6)	3" (76)			100	1000	
GT-40L2	14 1/2" (370)	0.14" (3.6)	4" (102)			100	1000	
GT-50S1	6 3/8" (160)	0.19" (4.8)	1 1/2" (38)	<i>STANDARD</i> 50 lbs (23.0 kg)	MS3367-1	100	1000	
GT-50S2	7 3/8" (188)	0.19" (4.8)	1 4/5" (46)			100	1000	
GT-50M	11 1/2" (300)	0.19" (4.8)	3" (76)			MS3367-7	100	1000
GT-50L1	14 1/2" (370)	0.19" (4.8)	4" (102)			MS3367-2	100	500
GT-50L2	17" (430)	0.19" (4.8)	4 9/16" (110)			100	500	
GT-120S	8" (200)	0.30" (7.6)	1 15/16" (50)	<i>LIGHT HEAVY DUTY</i> 120 lbs (54.4 kg)	MS3367-3	100	100	
GT-120M	14 1/2" (368)	0.30" (7.6)	4" (102)			100	100	
GT-120M1	17 3/4" (450)	0.30" (7.6)	5 1/5" (132)			100	100	
GT-175S	20 3/4" (528)	0.35" (9.0)	5 1/2" (140)	<i>HEAVY DUTY</i> 175 lbs (79.4 kg)		100	100	
GT-175M	24" (609)	0.35" (9.0)	7" (178)			100	100	
GT-175L1	28" (710)	0.35" (9.0)	7 1/2" (190)			100	100	
GT-175L2	32" (812)	0.35" (9.0)	9 7/16" (239)			100	100	
GT-175L3	36" (912)	0.35" (9.0)	10 1/3" (263)			100	100	
GT-175L4	42" (1070)	0.35" (9.0)	12 3/5" (320)			100	100	
GT-175L5	48" (1220)	0.35" (9.0)	14 3/8" (365)	100	100			