


CABLE CLAMPS

GCC | SERIES




- Insert cables in and clamp down with a screw
- Screw-mounts to any hard surface
- Open design for easy cable entry
- Manufactured from 100% virgin-grade Nylon 6/6
- Self-extinguishing 94V-2
- Operating temperature range of -40°F (-4°C) to 185°F (85°C)
- Available in natural (code -9) or UV resistant black (code -0)



PART NUMBER	MAX BUNDLE DIAMETER <i>Inches (mm)</i>	LENGTH <i>Inches (mm)</i>	WIDTH <i>Inches (mm)</i>	THICKNESS <i>Inches (mm)</i>	SCREW SIZE	PACKAGING	
						STD.	BULK
GCC-18	1/8" (3.2)	0.63" (16.0)	0.36" (9.1)	0.059" (1.5)	#10	100	1000
GCC-316	3/16" (4.8)	0.73" (18.5)	0.36" (9.1)		#10	100	1000
GCC-14	1/4" (6.4)	0.77" (19.6)	0.36" (9.1)		#10	100	1000
GCC-516	5/16" (8.0)	0.83" (21.1)	0.36" (9.1)		#10	100	1000
GCC-38	3/8" (9.5)	0.88" (22.6)	0.36" (9.2)		#10	100	1000
GCC-12	1/2" (12.7)	1.12" (28.5)	0.50" (12.7)		#10	100	1000
GCC-916	9/16" (14.3)	1.20" (30.5)	0.50" (12.7)		#10	100	1000
GCC-34	3/4" (19.1)	1.43" (36.3)	0.50" (12.7)		#10	100	1000
GCC-118	1 1/8" (28.6)	1.83" (46.5)	0.50" (12.7)		#10	100	1000

TWIST LOCKS

GTL | SERIES



- "Purse-lock" style clamp for extremely fast bundling and unbundling
- Excellent for cable organization
- Manufactured from 100% virgin-grade Nylon 6/6
- Self-extinguishing 94V-2
- Operating temperature range of -40°F (-4°C) to 185°F (85°C)



PART NUMBER	MAX BUNDLE DIAMETER <i>Inches (mm)</i>	LENGTH <i>Inches (mm)</i>	COLOR	PACKAGING	
				STD.	BULK
GTL-E	0.18" (4.5)	0.83" (21.0)	Natural	100	1000
GTL-G	0.41" (10.5)	1.22" (30.9)	Natural	100	1000
GTL-H	0.55" (14.0)	1.38" (35.1)	Natural	100	1000
GTL-K	0.87" (22.0)	1.79" (45.5)	Natural	100	1000