





TWIST-ON WIRE CONNECTORS

GWN | WINGED SERIES



GWN Winged Twist-On Wire Connectors features:

- UL Listed, CSA Approved components
- Flame retardant thermoplastic insulation shell
- Fixed internal wire spring secures connection with optimum conductivity
- Anti-slip winged grips for better twisting efficiency and comfort
- Deep skirt, offering superior protection against shorts and flashovers
- Threaded funnel entry smoothly guides wires into the connector



PART NUMBER	COLOR	A (in/mm)	B (in/mm)	C (in/mm)	A.W.G.	VOLTAGE	TEMP (°C / °F)	PACKAGING	
								STD. [†]	BULK
GWN-11	Yellow	1.016 25.8	0.717 18.2	0.386 9.8	18-10	600V UL* 300V CSA	105 / 221	100	500
GWN-12	Tan	1.142 29.0	0.720 18.3	0.457 11.6	22-8	600V UL* 300V CSA	105 / 221	100	500
GWN-13	Red	1.252 31.8	0.906 23.0	0.531 13.5	18-8	600V UL* 300V CSA	105 / 221	100	500
GWN-15	Grey	1.311 33.3	1.000 25.5	0.587 14.9	18-8	600V	105 / 221	100	250
GWN-17	Blue	1.575 40.0	1.260 32.0	0.740 18.8	14-6	600V	105 / 221	100	100
GWN-99	Green	1.134 28.8	0.795 20.2	0.476 12.1	14-10	GROUNDING CONNECTOR <i>with built-in through-port</i>		100	500

* Square cross-sectional wire spring. Rated 1,000V maximum in lighting fixtures and signs.

[†] Retail boxes are available for a nominal surcharge



GWS | POWER TOOL SOCKETS

Our GWS twist-on wire connector sockets attach to any standard 1/4" hexbits (like those on conventional power tools), allowing for quick and secure twist-on fastening.

The **GWS-3** is designed to accommodate the following Greenlite GWN series connectors: 11, 12, 13, 15, and 99