

BULLETS

GBF | FEMALE SERIES

Maximum Electrical Current:


22-16 A.W.G.: 10 amperes
 16-14 A.W.G.: 15 amperes
 12-10 A.W.G.: 24 amperes

Maximum Electrical Rating:

75 °C (167 °F)
 300 volts

Insulation Material: Vinyl

Terminal Material: Brass (tin-plated)



WIRE RANGE A.W.G.	PART NUMBER	BULLET DIAMETER	DIMENSIONS (inches/mm)						BULK QTY
			W	F	L	B	D	C	
22-16	GBF-R156V	0.156"	0.153	0.287	0.846	0.394	0.157	0.067	1000
			3.9	7.3	21.5	10.0	4.0	1.7	
16-14	GBF-B156V	0.156"	0.153	0.287	0.846	0.394	0.197	0.091	1000
			3.9	7.3	21.5	10.0	4.5	2.3	
	GBF-B195V	0.195"	0.193	0.276	0.846	0.394	0.197	0.134	1000
			4.9	7.0	21.5	10.0	4.5	3.4	

BULLETS

GBM | MALE SERIES

Maximum Electrical Current:


22-16 A.W.G.: 10 amperes
 16-14 A.W.G.: 15 amperes
 12-10 A.W.G.: 24 amperes

Maximum Electrical Rating:

75 °C (167 °F)
 300 volts

Insulation Material: Vinyl

Terminal Material: Brass (tin-plated)



WIRE RANGE A.W.G.	PART NUMBER	BULLET DIAMETER	DIMENSIONS (inches/mm)						BULK QTY
			W	F	L	B	D	C	
22-16	GBM-R156V	0.156"	0.157	0.335	0.827	0.394	0.157	0.067	1000
			4.0	8.5	21.0	10.0	4.0	1.7	
16-14	GBM-B156V	0.156"	0.157	0.335	0.827	0.394	0.177	0.091	1000
			4.0	8.5	21.0	10.0	4.5	2.3	
	GBM-B195V	0.195"	0.197	0.335	0.827	0.394	0.177	0.134	1000
			5.0	8.5	21.0	10.0	4.5	3.4	